

D1504 series 15X15X4mm(0.59"X0.59"X0.16")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Sleeve Bearing
OPERATING TEMPERATURE	-10 °C to +60 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	1.5g
ROHS COMPLIANCE	Yes
APPLICATIONS	Mini Projector

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D1504V3HS	3.3	0.045	0.15	10000	0.06	1.5	0.3	0.008	25
D1504V5HS	5.0	0.055	0.28	16000	0.11	2.8	0.4	0.011	35

DIMENSION

AIR PERFORMANCE

