

D17051 Series Ø170X51mm(Ø6.7"X2")
[View WebPage](#)
[View 3D Object](#)


HOUSING	Thermoplastic PBT, UL94V - 0
IMPELLER	Thermoplastic PBT, UL94V - 0
BEARING	Ball
OPERATING TEMPERATURE	-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute
WEIGHT	730g
ROHS COMPLIANCE	Yes

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D17051V24HB	24	0.8	19.2	3400	0.62	15.7	216	6.12	60
D17051V24MB	24	0.6	14.4	2900	0.54	13.9	202	5.69	56
D17051V24LB	24	0.45	10.8	2400	0.38	9.6	160	5.04	51
D17051V48HB	48	0.4	19.2	3400	0.62	15.7	216	6.12	60
D17051V48MB	48	0.35	16.8	2900	0.54	13.9	202	5.69	56
D17051V48LB	48	0.25	12	2400	0.38	9.6	160	5.04	51

DIMENSION
AIR PERFORMANCE
