

D1804 series 18X18X4mm(0.71"X0.71"X0.16")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Sleeve Bearing
OPERATING TEMPERATURE	-10 °C to +60 °C
INSULATION RESISTANCE	10 meg Ohms Min. @500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	17g
ROHS COMPLIANCE	Yes
APPLICATIONS	Mini Projector

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D1804V3HS	3.3	0.050	0.165	8500	0.077	1.95	0.65	0.018	25
D1804V5HS	5.0	0.055	0.275	13000	0.138	3.50	0.90	0.026	35

DIMENSION

AIR PERFORMANCE

