

D3510-A Series 35X35X10mm (1.38"X1.38"X0.4")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Plastic,UL94V-0
IMPELLER	Plastic,UL94V-0
BEARING	Ball
OPERATING TEMPERATURE	-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC(Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute(Between Frame and Terminal)
WEIGHT	9.0g
ROHS COMPLIANCE	Yes

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D3510V5S-A	5	0.05	0.25	9500	0.060	1.52	3.30	0.093	15.0
D3510V5H-A	5	0.10	0.48	8000	0.100	2.54	5.10	0.144	27.5
D3510V5M-A	5	0.11	0.55	7000	0.131	3.33	6.00	0.170	30.0
D3510V5L-A	5	0.18	0.90	4500	0.174	4.42	7.10	0.201	37.5
D3510V12S-A	12	0.06	0.72	9500	0.100	2.54	5.10	0.144	27.5
D3510V12H-A	12	0.06	0.72	8000	0.131	3.33	6.00	0.170	30.0
D3510V12M-A	12	0.09	1.08	7000	0.174	4.42	7.10	0.201	37.5

DIMENSION

AIR PERFORMANCE

