

D4007 Series 40X40X7mm (1.57"X1.57"X0.28")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball
OPERATING TEMPERATURE	-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	8g
ROHS COMPLIANCE	Yes

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D4007V5SLB	5	0.25	1.3	7500	0.13	3.25	6.51	0.18	34
D4007V5HB	5	0.23	1.2	6500	0.10	2.44	5.40	0.15	30
D4007V12HB	12	0.13	1.6	7500	0.13	3.25	6.51	0.18	34
D4007V12MB	12	0.11	1.3	6500	0.10	2.44	5.40	0.15	30

DIMENSION

AIR PERFORMANCE

