

DB12131-C Series 120.7X120.7X31mm(4.75"X4.75"X1.22")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Plastic with Fiber Glass Filled UL 94V-0
IMPELLER	Plastic with Fiber Glass Filled UL 94V-0
BEARING	Ball Bearing or Sleeve Bearing
OPERATING TEMPERATURE	Sleeve Bearing:-10 °C to +70 °C Ball Bearing:-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	260g
ROHS COMPLIANCE	Yes

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
DB12131V12H-C	12	0.60	7.2	2700	0.60	15.2	25	0.70	45
DB12131V24H-C	24	0.33	7.9	2700	0.60	15.2	25	0.70	45

DIMENSION

AIR PERFORMANCE

